

**Amendments to the Claims:**

1. (Currently amended) An apparatus capable of displaying a logo capable of glowing, comprising:

a light source capable of emitting light, wherein the light source is capable of emitting a plurality of particular colors, and wherein the light source is configured to emit a particular color of the plurality of particular colors according to a state of the computer system and to emit another particular color according to another state of the computer system; and

a translucent portion corresponding to the logo, wherein the translucent portion is capable of receiving the light from the light source and is capable of allowing the light to propagate therethrough.

2. (Cancelled)

3. (Original) An apparatus, according to claim 1, wherein the light source is disposed behind the translucent portion.

4. (Original) An apparatus, according to claim 1, wherein the light source comprises at least one light-emitting diode.

5. (Original) An apparatus, according to claim 1, wherein the light source is a lamp selected from the group consisting of an incandescent lamp, a neon lamp, and a fluorescent lamp.

6. (Original) An apparatus, according to claim 1, wherein the translucent portion has a back surface and the apparatus further comprises a light box capable of reflecting the light emitted by the light source toward the back surface of the translucent portion.

7. (Original) An apparatus, according to claim 6, wherein the light box comprises:  
a rear opening adapted to receive the light source;

a front opening capable of emitting the light from the light source, and  
a wall extending therebetween capable of reflecting the light emitted from the light source  
toward the front opening,  
wherein the front opening is adjacent the back surface of the translucent portion.

8. (Original) An apparatus, according to claim 7, wherein the wall comprises an inner surface having a matte finish.

9. (Original) An apparatus, according to claim 1, further comprising a bezel, wherein the translucent portion is disposed in the bezel.

10. (Original) An apparatus, according to claim 9, wherein the translucent portion has a back surface and the apparatus further comprises a light box capable of reflecting the light emitted by the light source toward the back surface of the translucent portion.

11. (Original) An apparatus, according to claim 9, wherein the translucent portion has a back surface and the apparatus further comprises a light box capable of reflecting the light emitted by the light source toward the back surface of the translucent portion, wherein the light box comprises:

a rear opening adapted to receive the light source;  
a front opening capable of emitting the light from the light source; and  
a wall extending therebetween capable of reflecting the light emitted from the light source toward the front opening,  
wherein the front opening is adjacent the back surface of the translucent portion.

12. (Original) An apparatus, according to claim 11, wherein the wall comprises an inner surface having a matte finish.

13. (Original) An apparatus, according to claim 9, wherein the translucent portion has a back

surface and the apparatus further comprises a light box capable of reflecting the light emitted by the light source toward the back surface of the translucent portion, wherein the light box comprises:

- a rear opening adapted to receive the light source;
- a front opening capable of emitting the light from the light source; and
- a wall extending therebetween capable of reflecting the light emitted from the light source toward the front opening, wherein:
  - the front opening is adjacent the back surface of the translucent portion;
  - the bezel has a rear surface; and
  - the light box is attached to the rear surface of the bezel.

14. (Original) An apparatus, according to claim 13, wherein the wall comprises an inner surface having a matte finish.

15. (Original) An apparatus, according to claim 13, wherein the light box is heat staked to the rear surface of the bezel.

Claims 16 - 19 (Cancelled)

20. (Original) An apparatus for displaying a logo capable of glowing, comprising:

- a light source capable of emitting light, wherein the light source is capable of emitting a plurality of particular colors, and wherein the light source is configured to emit a particular color of the plurality of particular colors according to a state of the computer system and to emit another particular color according to another state of the computer system;
- a bezel; and
- a logo badge comprising:
  - a translucent portion corresponding to the logo, wherein the translucent portion is capable of receiving the light from the light source and propagating the light therethrough;
  - and

a background portion generally surrounding at least a portion of the translucent portion, wherein the logo badge is disposed in the bezel.

21. (Cancelled)

22. (Original) An apparatus, according to claim 20, wherein the light source comprises at least one light-emitting diode.

23. (Original) An apparatus, according to claim 20, wherein the light source comprises a lamp selected from the group consisting of an incandescent lamp, a neon lamp, and a fluorescent lamp.

24. (Original) An apparatus, according to claim 20, wherein the translucent portion has a back surface and the apparatus further comprises a light box capable of reflecting the light emitted by the light source toward the back surface of the translucent portion.

25. (Original) An apparatus, according to claim 24, wherein the light box comprises:  
a rear opening adapted to receive the light source;  
a front opening capable of emitting the light from the light source; and  
a wall extending therebetween capable of reflecting the light emitted from the light source toward the front opening,  
wherein the front opening is adjacent the back surface of the translucent portion.

26. (Original) An apparatus, according to claim 25, wherein the wall comprises an inner surface having a matte finish.

27. (Original) An apparatus, according to claim 24, wherein the translucent portion has a back surface and the apparatus further comprises a light box capable of reflecting the light emitted by the light source toward the back surface of the translucent portion, wherein the light box comprises:

a rear opening adapted to receive the light source;

a front opening capable of emitting the light from the light source; and  
a wall extending therebetween capable of reflecting the light emitted from the light source  
toward the front opening,  
wherein the front opening is adjacent the back surface of the translucent portion.

28. (Original) An apparatus, according to claim 27, wherein the wall comprises an inner surface having a matte finish.

29. (Original) An apparatus, according to claim 24, wherein the translucent portion has a back surface and the apparatus further comprises a light box capable of reflecting the light emitted by the light source toward the back surface of the translucent portion, wherein the light box comprises:

a rear opening adapted to receive the light source;  
a front opening capable of emitting the light from the light source; and  
a wall extending therebetween capable of reflecting the light emitted from the light source toward the front opening, wherein:  
the front opening is adjacent the back surface of the translucent portion;  
the bezel has a rear surface; and  
the light box is attached to the rear surface of the bezel.

30. (Original) An apparatus, according to claim 29, wherein the wall comprises an inner surface having a matte finish.

31. (Original) An apparatus, according to claim 29, wherein the light box is heat staked to the rear surface of the bezel.

32. (Original) A computer system, comprising:

a chassis;  
a light source capable of emitting light, wherein the light source is capable of emitting a plurality of particular colors, and wherein the light source is configured to emit a

particular color of the plurality of particular colors according to a state of the computer system and to emit another particular color according to another state of the computer system; and

a bezel adjacent the chassis, wherein the bezel comprises a logo capable of receiving the light emitted by the light source and the logo is capable of allowing the light to propagate therethrough.

33. (Cancelled)

34. (Original) A computer system, according to claim 32, wherein the light source comprises at least one light-emitting diode.

35. (Original) A computer system, according to claim 32, wherein the light source comprises a lamp selected from the group consisting of an incandescent lamp, a neon lamp, and a fluorescent lamp.

36. (Original) A computer system, according to claim 32, wherein the light source is attached to the chassis.

37. (Original) A computer system, according to claim 32, wherein the logo comprises a translucent portion.

38. (Original) A computer system, according to claim 32, further comprising a light box capable of reflecting the light emitted by the light source toward the logo.

39. (Original) A computer system, according to claim 38, wherein the translucent portion has a back surface and the apparatus further comprises a light box capable of reflecting the light emitted by the light source toward the back surface of the translucent portion, wherein the light box comprises:

a rear opening adapted to receive the light source;

a front opening capable of emitting the light from the light source; and  
a wall extending therebetween capable of reflecting the light emitted from the light source  
toward the front opening,  
wherein the front opening is adjacent the back surface of the translucent portion.

40. (Original) An apparatus, according to claim 39, wherein the wall comprises an inner surface having a matte finish.

41. (Original) A computer system, according to claim 38, wherein the translucent portion has a back surface and the apparatus further comprises a light box capable of reflecting the light emitted by the light source toward the back surface of the translucent portion, wherein the light box comprises:

a rear opening adapted to receive the light source;  
a front opening capable of emitting the light from the light source; and  
a wall extending therebetween capable of reflecting the light emitted from the light source toward the front opening, wherein:  
the front opening is adjacent the back surface of the translucent portion;  
the bezel has a rear surface; and  
the light box is attached to the rear surface of the bezel.

42. (Original) An apparatus, according to claim 41, wherein the wall comprises an inner surface having a matte finish.

43. (Original) A computer system, according to claim 41, wherein the light box is heat staked to the rear surface of the bezel.

44. (Original) A computer system, according to claim 32, further comprising:

a processing unit;  
a power source; and  
a switch electrically interconnected with the light source and the processing unit,

wherein power from the power supply is supplied to the processing unit and the light source when the switch is in a closed position.

Claims 45-63 (Cancelled)